

SPECIFICATIONS

MODEL: A2123-HBT

- 1-1. Rated Voltage : 230 VAC 50/60 HZ
- 1-2. Operating Voltage Range : 185-245 VAC
- 1-3. Starting Voltage : 185 VAC
- 1-4. Rated Speed : 2500/2750 RPM ± 10%
- 1-5. Air Delivery : 112/124 CFM
- 1-6. Static Pressure : 0.28/0.31 Inch-H₂O
- 1-7. Rated Current : 0.14/0.12 AMP
- 1-8. Input Power : 24/22 WATTS
- 1-9. Noise Level : 44/47 dB(A)
- 1-10. Direction of Rotation : Counter-clockwise viewed front fan blade
- 1-11. Motor Protection : Impedance Protected.
- 1-12. Operating Temperature : -10 to +70 Deg.C
- 1-13. Storage Temperature : -40 to +70 Deg.C
- 1-14. Bearing System : Precise ball bearing system
- 1-15. Weight : 536g
- 1-16. Vibration : Vibration of acceleration 1.5G and Frequency 5~50~5Hz is applied in the 3 directions(X,Y,Z) for 30 minutes, each Direction at the cycle of 1 minute.

建準電機工業股份有限公司
 SUNONWEALTH ELECTRIC
 MACHINE INDUSTRY CO., LTD

SPEC. NO.	A120418	REVISE DATE	
ISSUE DATE	04. 16. 2001	EDITION	99. 4. 20
PAGE	3 OF 6		

