

## MYC-YA157C CPU Module

- STMicroelectronics STM32MP1 MPU based on 650MHz Dual Arm Cortex-A7 and 209MHz Cortex-M4 Cores
- 512MB DDR3, 4GB eMMC Flash
- On-board Gigabit Ethernet PHY
- 1.0mm pitch 164-pin Stamp Hole Expansion Interface
- Supports Running Linux OS




Figure 1-1 MYC-YA157C CPU Module (delivered with shielding cover by default)

Measuring only 45mm by 43mm, the [MYC-YA157 CPU Module](#) is a compact [ST STM32MP1](#) powered System-on Module (SoM) that combines the [STM32MP157](#) processor ([STM32MP157AAC3](#)), 512MB DDR3, 4GB eMMC as well as an integrated GigE PHY chip. A number of peripherals and IO signals are brought out through 1.0 mm pitch 164-pin stamp-hole (Castellated-Hole) expansion interface to make the module an excellent embedded controller for your system integration. Typical applications are industrial control, consumer electronics, smart home, medical and more other energy-efficient applications which require rich performance and low power.





Figure 1-2 MYC-YA157C CPU Module


The [MYC-YA157C](#) is running Linux OS. Based on Linux 5.4.31 kernel, MYIR provides abundant software resources for Yocto 3.1 based MYIR MEasy-HMI system, Yocto 3.1 based ST Weston system, Yocto 3.1 based MYIR MEasy-IOT system and Ubuntu 18.04 system including kernel and driver source code, STM32CubeProgrammer and STM32CubeMX tools to enable users to start their development rapidly and easily.

The [MYD-YA157C development board](#) is built around the [MYC-YA157C CPU Module](#). It takes full advantages of the STM32MP157A MPU to explore a rich set of peripherals and interfaces to the base board including RS232, RS485, USB Type-C DRP, USB2.0 HOST, Gigabit Ethernet, WiFi/Bluetooth, CAN, Micro SD Card Slot, JTAG, RGB888

based LCD/HDMI, MIPI-DSI, etc. The [MYD-YA157C development board](#) is delivered with one Quick Start Guide, one Type-C cable, one USB to TTL serial cable and one WiFi/Bluetooth antenna to provide user a complete platform for evaluating and prototyping based on STM32MP1 series microprocessors. MYIR also offers [MY-TFT070CV2 LCD Module](#) as an option for the board.



*Figure 1-3 MYD-YA157C Development Board Top-view*



*Figure 1-4 MYD-YA157C Development Board Bottom-view*

## Hardware Specification

The MYC-YA157C CPU Module is using STMicroelectronics [STM32MP157AAC3](#) Microprocessor with 12 x 12 mm, 0.5 mm pitch, TFBGA361 package which is among the [STM32MP1 Series](#). The STM32MP1 series is based on a heterogeneous single or dual Arm Cortex-A7 and Cortex-M4 cores architecture, strengthening its ability to support multiple and flexible applications, achieving the best performance and power figures at any time. The Cortex-A7 core provides access to open-source operating systems (Linux/Android) while the Cortex-M4 core leverages the STM32 MCU ecosystem. It is available in 3 different lines which are pin-to-pin compatible:

- [STM32MP157](#): Dual Cortex-A7 cores @ 650 MHz, Cortex-M4 core @ 209 MHz, 3D GPU, DSI display interface and CAN FD
  - [STM32MP153](#): Dual Cortex-A7 cores @ 650 MHz, Cortex-M4 core @ 209 MHz and CAN FD
  - [STM32MP151](#): Single Cortex-A7 core @ 650 MHz, Cortex-M4 core @ 209 MHz
- Each line comes with a security option (cryptography & secure boot)

Arm® Cortex®-A7 – 650 MHz

ACCELERATION			Cortex®-A7 core	f <sub>cpu</sub> (MHz)	Cortex®-M4 core	f <sub>mcu</sub> (MHz)	3D GPU	f <sub>gpu</sub> (MHz)	HW Crypto	FD-CAN	MIPI®-DSI
Product lines											
<ul style="list-style-type: none"><li>• Dual core Arm® Cortex®-A7 processor</li><li>• L1 and L2 caches</li><li>• 3D Graphic Processing Unit*</li><li>• Floating Point Unit + Arm® Neon™</li><li>• Arm® Cortex®-M4 209 MHz coprocessor</li><li>• MDMA + DMA</li><li>• LPDDR2/LPDDR3 16/32**-bit 533 MHz</li><li>• DDR3/DDR3L 16/32**-bit 533 MHz</li></ul>	STM32MP151A		1	650	1	209	-	-	-	-	-
	STM32MP151C								•	-	-
	STM32MP153A		2	650	1	209	-	-	-	-	-
	STM32MP153C								•	-	-
	STM32MP157A		2	650	1	209	•	533	-	-	•
	STM32MP157C								•	•	•
CONNECTIVITY											
<ul style="list-style-type: none"><li>• 2 x USB2.0 HS Host</li><li>• USB2.0 OTG FS/HS</li><li>• 3 x SDMMC/SDIO</li><li>• USART, UART, SPI, I²C</li><li>• 2 x (TT)FD-CAN2.0*</li><li>• Gigabit Ethernet IEEE 1588***</li><li>• FMC (NAND Flash)</li><li>• Camera VF</li><li>• Dual mode Quad-SPI</li><li>• DSI 2 Gbit/s*</li></ul>											

Notes:

\* Not available in all product lines

\*\* 16/32-bit for LFBGA448 and TFBGA361 packages, 16-bit only for LFBGA354 and TFBGA257 packages

\*\*\* 10/100M Ethernet only for LFBGA354 and TFBGA257 packages

Figure 1-5 STM32MP1 Series Processors






Figure 1-6 STM32MP157 Block Diagram

**Mechanical Parameters**

- Dimensions: 45mm x 43mm
- PCB Layers: 8-layer design
- Power supply: +5V/0.5A
- Working temperature: 0~70 Celsius (commercial grade) or 40~85 Celsius (industrial grade)

**Processor**

- STMicroelectronics STM32MP157AAC3 Microprocessor
  - Up to 650MHz dual-core Arm Cortex-A7 32-bit RISC core
  - Up to 209MHz Arm Cortex-M4 32-bit RISC core with FPU/MPU
  - Integrated 3D GPU

**Memory**

- 512MB DDR3 (supports up to 1GB DDR3)
- 4GB eMMC Flash (supports up to 64GB eMMC)
- Nand Flash (alternative design with eMMC, supporting 256MB / 512MB / 1GB Nand Flash)

**Peripherals and Signals Routed to Pins**

- One 10/100/1000M Ethernet PHY
- 1.0mm pitch 164-pin Stamp Hole Expansion Interface
  - 8 x Serial ports
  - 6 x I2C
  - 6 x SPI
  - 1 x SAI
  - 1 x USB 2.0 Host and 1 x USB 2.0 OTG
  - 2 x SDIO
  - 2 x CAN
  - 1 x MIPI-DSI
  - 1 x Digital Camera Interface (DCMI)
  - 1 x RGB Interface (supports RGB888, resolution up to 1366 x 768 @60fps)
  - Up to 97 GPIOs

*Note: the peripheral signals brought out to the expansion interface are listed in maximum number. Some signals are reused. Please refer to the processor datasheet and the CPU Module pinout description file.*




Figure 1-7 MYC-YA157C CPU Module Function Block Diagram




Figure 1-8 MYC-YA157C Dimensions Chart

## Software Features

Item	Features	Description	Source Code
Bootstrap program	TF-a-2.2	Arm Trusted Firmware	YES
Bootloader	U-boot-2020.01	Kernel bootstrap	YES
Linux kernel	Linux-5.4.31	Customized based on ST kernel_5.4.31 version for MYD-YA157C	YES
Drivers	Nand Flash	Nand Flash driver	YES
	PMIC	STPMIC driver	YES
	USB Host	USB Host driver	YES
	USB OTG	USB OTG driver	YES
	I2C	I2C driver	YES
	SPI	SPI driver	YES
	Ethernet	10M/100M/1000M Ethernet driver	YES
	MMC	eMMC/TF card driver	YES
	LCD	LCD driver, supports MYIR's 7-inch LCD with 800 x 480 pixels resolution	YES
	HDMI	HDMI driver	YES
	Touch	Capacitive touch screen driver	YES
	PWM	PWM driver	YES
	RTC	RTC driver	YES
	GPIO	GPIO driver	YES
	UART/USART	Serial port driver	YES
	CAN	FDCAN Bus driver	YES
	RS485	RS485 driver	YES
	Camera	USB Camera driver (OV2659)	YES
	WiFi & BT	AP6212 WiFi/BT driver (SDIO)	YES
	Watchdog	Watchdog driver	YES
File system	rootfs	Yocto 3.1 for ST Weston system	YES
	rootfs	Yocto 3.1 for QT5.12 system	YES
	rootfs	MEasy-IOT 1.0 & MEasy_HMI 2.0 demo system developed by MYIR	YES
	Ubuntu core system	Based on ubuntu18.04	YES
Tools	STM32CubeProgrammer	ST programmer software	BIN
	STM32CubeMX	ST configuration integration tool	BIN
Applications	GPIO LED	LED example	YES
	GPIO KEY	KEY example	YES
	NET	TCP/IP Socket C/S example	YES
	RTC	RTC example	YES
	RS232	RS232 example	YES
	RS485	RS485 example	YES
	CAN	CAN example	YES
	LCD	LCD Display example	YES
	Camera	Camera Display example	YES
	UART	UART example	YES
Compiler Tool Chain	Cross compiler	arm-openstlinux_weston-linux-gnueabi	BINARY

Table 1-1 MYD-YA157C Software Features

The MYD-YA157C runs Linux OS and is provided with software packages. Based on Linux 5.4.31 kernel, MYIR has provided abundant software resources for Yocto 3.1 based MYIR MEasy-HMI system, Yocto 3.1 based ST Weston system, Ubuntu 18.04 system and MYIR MEasy-IOT system including kernel and driver source code, STM32CubeProgrammer and STM32CubeMX tools to enable users to start their development rapidly and easily.




Figure 1-7 MEasy-HMI System Structure




Figure 1-8 MEasy-IOT System Structure



## Order Information

Product Item	Part No.	Packing List
MYC-YA157C CPU Module	MYC-YA157C-V2-4E512D-65-C	➤ One MYC-YA157C CPU Module
	MYC-YA157C-V2-4E512D-65-I	
MYD-YA157C Development Board	MYD-YA157C-V2-4E512D-65-C	➤ One MYD-YA157C Development Board (including MYC-YA157C CPU Module) ➤ One USB Type-C cable ➤ One USB to UART Serial cable ➤ One WiFi/Bluetooth Antenna ➤ One Quick Start Guide
	MYD-YA157C-V2-4E512D-65-I	



### MYiR Tech Limited

Room 04, 6th Floor, Building No.2, Fada Road, Yunli Smart Park,  
Bantian, Longgang District, Shenzhen, Guangdong, China 518129

E-mail: [sales@myirtech.com](mailto:sales@myirtech.com)

Phone: +86-755-22984836

Fax: +86-755-25532724

Website: <http://www.myirtech.com>