

S/M/L

NEW

XS

NEW


XS

## GUIDING DIALOGUE

## Protection class IP 40

## Max. size of PCB (L x W in mm)

	bottom part	top part
XS	120 x 115	127 x 115
S	120 x 180	120 x 180
M	180 x 180	180 x 180
L	240 x 180	240 x 180



## THE PRODUCT

You can hardly present your communication and network equipment in a more attractive way.

DIATEC is an attractive eye-catching design for living and working environments. But this innovative range of cases also offers many functional benefits.

All design features are perfectly integrated. Depending on your requirements, different equipment options and connections are possible.

## YOUR ADVANTAGE

Modern, flat enclosure design, ideal for table top and wall mounting applications.

Plain, recessed area on the bottom part for installation and protection of interfaces, screwed cable glands, plug-in connections etc.

Easy, invisible wall mounting.

Recessed operating area on the top for the protection of the membrane keyboards and operating elements.





## PRESTIGIOUS



### SIZES S/M/L

Separate slot-in panels can be used as interior partitions, for example to guard the electronics when changing batteries. This allows the complete pre-assembly of the electronics unit. The technician on site only has to mount the unit on the wall and connect up the relevant cables. Connection can be effected from the left and/or from the right-hand side. The actual case does not have to be opened to do this, only the snap-on side trims.

Accessory hinged lids, in case colour or transparent plastic, protect the dialogue zone.

### APPLICATIONS

Systems for data collection on the job.

Access and security controls.

Peripheral equipment for computers, data system engineering.

Measuring and controlling.

Medical field and laboratory technology.

### Design DIATEC XS


Two-piece case, consisting of top and bottom part, screwed together. Integrated battery holder for 2 x 1.5 V AA batteries. Pre-shaped flush-mounting box contoured in the bottom part.

### DIATEC S, M, L

Four-piece case, consisting of top and bottom part as well as two covers for concealing the assembly screws. If required, the snap-on covers can be locked to prevent unauthorised access. Integrated battery compartment for 2 x 1.5 V AA batteries or 1 x 9 V flat battery.

assembly instruction see our website  
[www.okw.com](http://www.okw.com)


## DIATEC

DIATEC	Size	Outside dim. in mm			Equipment (dim. in mm) max. dim. keypad	Material	Part-No.	
		L	W	H			off-white RAL 9002	lava
	XS* <sup>1</sup> <b>NEW</b>	155	150	37	91.20 x 91.20	ABS (UL 94 HB)	A 90 92 107	A 90 92 108
	S* <sup>2</sup>	200	210	48	127.60 x 119.70	ABS (UL 94 HB)	A 90 93 107	A 90 93 108
	M* <sup>2</sup>	200	270	48	127.60 x 179.60	ABS (UL 94 HB)	A 90 94 107	A 90 94 108
	L* <sup>2</sup> <b>NEW</b>	200	330	48	127.60 x 239.60	ABS (UL 94 HB)	A 90 95 107	A 90 95 108

## DIATEC ACCESSORIES

Article	For DIATEC	Version / Application	Part-No.		
			ABS, case colour* <sup>3</sup>	PC, translucent* <sup>4</sup>	PC, clear* <sup>4</sup>
① Hinged lid	S, L (off-white)* <sup>5</sup>	2 mounting holes ø 4.2 mm necessary, 1 set	A 91 93 127	A 91 93 121	A 91 93 131
	S, L (lava)* <sup>5</sup>	2 mounting holes ø 4.2 mm necessary, 1 set	A 91 93 128	A 91 93 122	A 91 93 132
	M (off-white)	2 mounting holes ø 4.2 mm necessary, 1 set	A 91 94 127	A 91 94 121	A 91 94 131
	M (lava)	2 mounting holes ø 4.2 mm necessary, 1 set	A 91 94 128	A 91 94 122	A 91 94 132

Article	For DIATEC	Version / Application	Part-No.
② Slot-in panel	S, M, L	ABS, off-white, 156 x 30 x 3 mm, 1 pc	A 91 94 007
③ Set of battery clips <b>NEW</b>	XS	nickel-plated for 2 x 1.5 V mignon cells (AA)	A 91 90 015
	S, M, L	tin-plated for 2 x 1.5 V mignon cells (AA)	A 91 90 002
④ Plug-in contact	S, M, L	for one 9 V flat battery (PP3), 1 pc	A 91 60 003
⑤ Non-slip pads	XS	transparent, self-adhesive, secure non-slip desk top positioning, 1 pair	A 92 07 150
	S, M, L	transparent, self-adhesive, secure non-slip desk top positioning, 1 pair	A 92 12 330
⑥ Self-tapping screw	XS, S, M, L	ø 3 x 6 mm (PZ1), for mounting PCBs, 1 pc	A 03 06 031
⑦ Torx screwdriver T10 <b>NEW</b>	XS	Torx 10, with ergonomic handle, for assembling enclosure	A 03 99 T10



universal accessories on pages 178-187

\*<sup>1</sup> supply: 1 bottom and top part each, assembly kit;  
assembly of bottom and top part with 2 Torx T10 self-tapping screws, stainless steel

\*<sup>2</sup> supply: 1 bottom and top part each, 1 trim left and right side incl. 2 locking elements, assembly kit;  
assembly of top and bottom part with 4 self-tapping screws (PZ2), snap-on side trims. If required, the trims can also be locked, thus preventing unauthorised access

\*<sup>3</sup> in the relevant case colour

\*<sup>4</sup> fasteners from the assembly set in the case colour in question

\*<sup>5</sup> hinged lid for covering the dialogue area of the DIATEC S or for partially covering the dialogue area of the DIATEC L (half side)